



Oznaczenie	Rozmiar		Ciężnienie robocze (bar)	Przepływ nominalny (l/min)	ØT	CH2	CH3	ØE	L1	L2	L3	Rozmiar gwintu (F)
	DNP	ISO										
D2FFN G 1/8	04	5	500	3	.	17	17	25	84	48,5	43,5	G 1/8
D2FFN G 1/4	06	6,3	400	12	.	22	22	28	100	58,5	52	G 1/4
D2FFN G 3/8	06	6,3	400	12	.	22	22	28	100	58,5	52	G 3/8
D2FFN G 1/2	13	12,5	350	23	.	30	30	32	118	73,5	60,5	G 1/2
D2FFN G 3/4	20	20	350	45	.	36	36	38	144	87	74,5	G 3/4
D2FFN G 1	25	25	350	100	.	41	41	48	161	97	86	G 1
D2FFN G 1 1/4	30	31,5	350	189	.	55	55	55	177	109,5	90	G 1 1/4

OZNACZENIA SZYBKOZŁĄCZY D2FFN (PLT4 IG) WG EUMAT I DNP

oznaczenie szybkozłączy wg Eumat	oznaczenie DNP		wymiar wg DNP
	Mufa	Stecker	
D2FFN G 1/8	PLT4.0404.112	PLT4.0404.113	04
D2FFN G 1/4	PLT4.0606.112	PLT4.0606.113	06
D2FFN G 3/8	PLT4.0610.112	PLT4.0610.113	06
D2FFN G 1/2	PLT4.1313.112	PLT4.1313.113	13
D2FFN G 3/4	PLT4.2019.112	PLT4.2019.113	20
D2FFN G 1	PLT4.2525.112	PLT4.2525.113	25
D2FFN G 1 1/4	PLT4.3031.112	PLT4.3031.113	30