



Oznaczenie	Rozmiar		Ciężnienie robocze (bar)	Przepływ nominalny (l/min)	ØT	CH2	CH3	ØE	L1	L2	L3	Rozmiar gwintu (F)
	DNP	ISO										
DCVV G 1/4	06	6,3	350	12	.	19	30	35	93	59	58	G 1/4
DCVV G 3/8	10	10	325	23	.	22	30	34	98	64	49	G 3/8
DCVV G 1/2	13	12,5	300	45	.	30	36	42	103	67	53	G 1/2
DCVV G 3/4	20	20	250	106	.	36	41	47,5	132	86	67	G 3/4
DCVV G 1	25	25	250	189	.	41	50	55	152	100	78	G 1
DCVV G 1 1/4	30	31,5	200	288	.	55	75	80	210	126	131	G 1 1/4
DCVV G 1 1/2	30	31,5	200	288	.	55	75	80	214	128	133	G 1 1/2

OZNACZENIA SZYBKOZŁĄCZY DCVV (PVV3 IG) WG EUMAT I DNP

oznaczenie szybkozłączy wg Eumat	oznaczenie DNP		wymiar wg DNP
	Mufa	Stecker	
DCVV G 1/4	PVV3.1006.112	PVV3.1006.113	06
DCVV G 3/8	PVV3.1010.112	PVV3.1010.113	10
DCVV G 1/2	PVV3.1313.112	PVV3.1313.113	13
DCVV G 3/4	PVV3.2019.112	PVV3.2019.113	20
DCVV G 1	PVV3.2525.112	PVV3.2525.113E	25
DCVV G 1 1/4	PVV3.3031.112	PVV3.3031.113	30
DCVV G 1 1/2	PVV3.3039.112	PVV3.3039.113	30