



Oznaczenie	Rozmiar		Ciężnienie robocze (bar)	Przepływ nominalny (l/min)	ØT	CH2	CH3	ØE	Rozmiar gwintu (F)			
	DNP	ISO							L1	L2	L3	
DNV M14x1,5 IG	13	12,5	225	45	.	30	30	38	109	72	59	M 14x1,5
DNV M16x1,5 IG	13	12,5	225	45	.	30	30	38	109	72	59	M 16x1,5
DNV M18x1,5 IG	13	12,5	225	45	.	30	30	38	109	72	59	M 18x1,5
DNV M20x1,5 IG	13	12,5	225	45	.	30	30	38	109	72	59	M 20x1,5
DNV M22x1,5 IG	13	12,5	225	45	.	30	30	38	109	72	59	M 22x1,5
DNV M26x1,5 IG	20	20	225	106	.	36	36	46	132	93,3	66	M 26x1,5
DNV M30x2 IG	25	25	225	189	.	41	41	54	142	99,5	76	M 30x2

OZNACZENIA SZYBKOZŁĄCZY DNV IG (PPV3 IG) WG EUMAT I DNP

oznaczenie szybkozłączy wg Eumat	oznaczenie DNP		wymiar wg DNP
	Mufa	Stecker	
DNV M14x1,5 IG	PPV3.1314.102	PPV3.1314.103	13
DNV M16x1,5 IG	PPV3.1316.102	PPV3.1316.103	13
DNV M18x1,5 IG	PPV3.1318.102	PPV3.1318.103	13
DNV M20x1,5 IG	PPV3.1320.102	PPV3.1320.103	13
DNV M22x1,5 IG	PPV3.1322.102	PPV3.1322.103	13
DNV M26x1,5 IG	PPV3.2026.102	PPV3.2026.103	20
DNV M30x2 IG	PPV3.2530.102	PPV3.2530.103	25